# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# **II CLIPSAL**



# Universal Dimmer Mechanism, Clipsal Iconic, Rotary 350 W

42E350RUD2M-VW

### Main

| Range   | Clipsal Iconic   |  |
|---|------------------|--|
| Product or component type   | Dimmer           |  |
| Device presentation   | Mechanism        |  |
| Dimmer type   | Universal        |  |
| Colour tint   | Vivid white (VW) |  |
| Type of packing   | Вох              |  |
| Dimmable LED - 350 W - 240 V AC Incandescent - 350 W - 240 V AC Low voltage halogen lamp with electronic transformer - 350 W - 240 V AC Dimmable fluocompact lamp - 150 W - 240 V AC Low voltage halogen lamp with iron core transformer - 350 W - 240 V AC Dimmable fluorescent - 150 W - 240 V AC |                  |  |

# Complementary

| control type                          | Rotary knob  |  |
|---------------------------------------|--|--|
| fixing mode                           | Clip-in  |  |
| Surface finish                        | Glossy   |  |
| Ambient air temperature for storage   | 060 °C   |  |
| Dimmer control                        | 315° rotary setting                                |  |
| [le] rated operational current        | 1.5 A  |  |
| [Ue] rated operational voltage        | 220240 V AC 50 Hz 1 W                              |  |
| Function available                    | Brightness adjustment                              |  |
| Protection type                       | Short-circuit                                      |  |
| Ambient air temperature for operation | 045 °C   |  |
| Relative humidity                     | 090 %  |  |
| Connections - terminals               | Flying leads                                       |  |
| Material                              | PC (UL94 V-2): top<br>PC MAS056 (UL94 V-2): bottom |  |
| Height                                | 22.5 mm  |  |
| Width                                 | 22.5 mm  |  |
| Depth                                 | 39 mm  |  |
| Embedding depth                       | 37 mm  |  |

# **Environment**

| Derating factor | 1 devices 350 W without derating<br>2 devices 250 W with derating factor<br>3 devices 150 W with derating factor |
|-----------------|--|
| Standards       | AS/NZS 60669.2.1   |

# **Packing Units**

| •                            |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 3.9 cm  |
| Package 1 Width              | 6.7 cm  |
| Package 1 Length             | 8.7 cm  |
| Package 1 Weight             | 60 g    |
| Unit Type of Package 2       | BB1     |
| Number of Units in Package 2 | 6       |
| Package 2 Height             | 10.2 cm |
| Package 2 Width              | 13 cm   |
| Package 2 Length             | 15.6 cm |
| Package 2 Weight             | 494 g   |



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint                             |                               |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 1                             |
| Environmental Disclosure                              | Product Environmental Profile |

### **Use Better**

| Packaging made with recycled cardboard | Yes                       |
|--|---------------------------|
| Packaging without single use plastic   | No                        |
| EU RoHS Directive                      | Compliant with Exemptions |
| REACh Regulation                       | REACh Declaration         |

### **Use Again**

| ○ Repack and remanufacture |                         |
|----------------------------|-------------------------|
| Circularity Profile        | End of Life Information |
| Take-back                  | No                      |