Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

II CLIPSAL



Switch Mechanism, 30 Series, 250V, 10A, 1 Way/2 Way

30M-DB

Main

Range of product	Series 30 Standard Series
Product brand	Clipsal
Assembly Type	Basic element

Complementary

•		
Number of poles	1	
Installation Type	Flush	
Number Of Switches	1	
Material	PVC (polyvinyl chloride)	
Local signalling	without	
[Ue] rated operational voltage	250 V AC	
Rated current	10 A	
Load type	Fluorescent lamp 10 A LEDi lamp 100 W	
Marking	Without marking	
Surface finish	Glossy	
Actuator	Rocker	
Switch function	1-pole	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 cm
Package 1 Width	2.36 cm
Package 1 Length	2.9 cm
Package 1 Weight	14 a



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint				
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1			
Environmental Disclosure	Product Environmental Profile			

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant with Exemptions	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
Circularity Profile	No need of specific recycling operations	
Take-back	No	