

Siena Wall Light Installation Instructions



Product Specifications

Model No.	HV3654T-BLK	HV3654T-WHT	HV3655T-BLK	HV3655T-WHT	HV3656T-BLK	HV3656T-WHT	HV3657T-BLK	HV3657T-WHT
Name	Siena							
Material	Aluminium							
Colour	Black	White	Black	White	Black	White	Black	White
IP Rating	IP54							
Installation Type	Wall - Surface Mounted							
Protection Class	1 (240v Requires Earth)							
Input Voltage	240v AC							
Lamp Base	Built in LED							
Lamp Wattage	1x 6w		2x 4.5w		1x 9w		2x 6w	
Colour Temp	TRI Colour - 3000k, 4000k, 5500k							
Lumens	230lm, 255lm, 235lm		2x 255lm, 2x 265lm, 2x 260lm		435lm, 470lm, 455lm		2x 345lm, 2x 350lm, 2x 345lm	
CRI	> 80							
Dimmable	Yes - Triac Dimming							
Warranty	3 Years Replacement*							

<p>HV3654 Dimensions</p>	<p>HV3655 Dimensions</p>	<p>HV3656 Dimensions</p>	<p>HV3657 Dimensions</p>
<p>HV3654 Mounting Base</p>	<p>HV3655 Mounting Base</p>	<p>HV3656 Mounting Base</p>	<p>HV3657 Mounting Base</p>

Important Safety Issues:

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation.
- Modification of this product will void any warranty.
- Havit Lighting does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- Aluminium and 304SS fittings must not be installed within 5km of any salt water environments.
- All o-rings and seals must be in place correctly to maintain warranty
- This form may be updated at any time due to product improvements, please check online installation form for most current version.

Steps for Installation:

1. Make sure that the electrical circuit is free of voltage (master switch off)
2. Loosen allen screws from side of fitting.
3. Remove base plate from fitting.
4. Slide cable through cable gland and place base plate against wall
5. Attach base plate to wall using appropriate screws for application.
6. Seal all holes including cable entry and around screws.
7. Connect the cable - use wire with earth; connect the earth first, then live and neutral wire.
8. Fitting is preset to 3000k, to change slide switch located inside base of fitting to desired colour temperature.
9. Reattach fitting to base plate making sure seals are still in place
10. Tighten allen screws making sure these are tight to avoid any water penetration.
11. Apply silicon around edge of fitting to prevent any water from getting inside to electrical connections.
12. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.

Must be installed by a licensed electrician

Contact Details:

143 Beauchamp Road
Matraville NSW 2036
Australia

Tel: 02 9381 8300
Fax: 02 9666 8881
Email: sales@havit.com.au
Web: www.havit.com.au

Warranty Terms & Conditions*



www.havit.com.au

