

## SHIELDER LED FLOODLIGHT WITH SENSOR



Improve your home security and safety with this Shielder sensor floodlight which turns on when movement is detected. The discreet and durable double floodlights can be easily adjusted to direct light where it is needed.

- Modern design that can be installed both on the wall and on the ceiling under the eaves.
- Durable UV stabilised polycarbonate offering you a rust free solution that is ideal for coastal environments.
- · Provides an even and bright illumination over a wide area
- Latest in ultra-bright LED technology
- · Advanced PIR motion sensing.
- Sensor range of 150 degrees x 2 metres
- · IP54 weather resistant for outdoor installation
- Light up the right area using the fully adjustable heads.

## **APPLICATIONS**

- Great for entrances, patios, gardens, exteriors walls and for lighting up walkways and large areas.
- Suitable for residential and commercial applications







## SHIELDER LED FLOODLIGHT WITH SENSOR

Operating voltage:	240V / 50Hz			
Class:	Class II (2)			
Wattage:	2 x 10W			
Lumens:	2100 lm			
Colour Temperature:	4200K			
Light adjustable:	No			
Dimming:	No			
Motion Detection:	Advanced PIR motion sensing			
Operation Modes:	Auto-Override			
PIR Range:	12 metres x 150 degrees			
Light Time On:	10 sec to 5 min.			
Lux Sensitivity:	5 ~ 2000lx			
Construction:	UV stablised polycarbonate			
Ingress protection:	IP54 rated			
Warranty:	3 year replacement			
Standards:				

## **INSTALLATION**

Must be installed by a licensed electrician





	MODEL	COLOUR	DESCRIPTION	BOX SIZE	GROSS WEIGHT	BOX QTY	BARCODE/TUN
RETAIL BOX	20784/05	White	Shielder LED 2 Light Floodlight with Sensor	W135 x H150 x D190 mm	0.68 kg	1 pc	9 312641 207856 >
OUTER CTN	20784/05	White	Shielder LED 2 Light Floodlight with Sensor	W285 x H320 x D400mm	5.44 kg	8 pc	19312641207853
RETAIL BOX	20784/06	Black	Shielder LED 2 Light Floodlight with Sensor	W135 x H150 x D190 mm	0.68 kg	1 pc	9 312641 207849 >
OUTER CTN	20784/06	Black	Shielder LED 2 Light Floodlight with Sensor	W285 x H320 x D400 mm	5.44 kg	8 pc	19312641207846