

IP45 RATED DUAL DOOR OUTDOOR FREESTANDING CABINET



DESCRIPTION

CERTECH IP rated racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. If you need a tough & robust rack, then look no further than CERTECH IP45 & IP65 rated racks, available in wall mounted & free-standing options. All racks are manufactured to universal 19" standards, providing the ability of use with universal 19" equipment from vendors worldwide. All racks are constructed from SGCC with a zinc powder coating or SUS316 stainless steel, and they are shipped fully assembled for quick deployment. CERTECH racks are covered by a 2-year warranty, subject to use within the static loading specifications and operation within normal environmental conditions.

FEATURES

- IP Rating
- Fans
- Cable Entry
- Rack Mounting Compatibility
- Vertical Mounting Rails
- Ventilation & Dust Filters
- Front & Rear Doors

DETAILS		
Rack Type	Free-Standing IP45 Rated	
Static Loading Capacity	800kgs	
Colour	Grey	
Material	SGCC+Zinc Powder Coated	
Mounting Hole Type	Square	
Security	Lockable front & rear doors	
Assembly	Fully Welded Construction	
Warranty (Rack)	2-year warranty. Subject to use within the static loading	
wallally (kack)	specifications and operation within normal environmental conditions	
Warranty (Fans)	1-year warranty	



IP45 RATED DUAL DOOR OUTDOOR FREESTANDING CABINET

NROD188X- 8GY-DD-V2	RU	WxDxH (External)	Shipping dimensions WxDxH
		849mm x 894mm x 1119mm	915mm x 880mm x 1280mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
	18RU	378mm	405mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an ing rails	angled gas-strut rain hood, front & rear adjustable mount-
NROD248X- 8GY-DD-V2	RU	WxDxH (External)	Shipping dimensions
- Construction of the Cons		849mm x 894mm x 1395mm	915mm x 880mm x 1520mm
		Set distance between front and rear mounting rails	Max useable space (front to rear door)
	24RU	378mm	405mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails	
NROD278X- 8GY-DD-V2	RU	WxDxH (External)	Shipping dimensions
control		849mm x 894mm x 1519mm	915mm x 880mm x 1650mm
	27RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)
9		378mm	405mm
		INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails	

www.certech.com.au • 1300 144 111 • info@certech.com.au ABN: 17 149 306 785



IP45 RATED CABINETS, OUTDOOR - DUAL DOOR

