

IP45 RATED OUTDOOR CABINET

Free standing outdoor cabinet

NRODXXXXX



DESCRIPTION

CERTECH IP rated racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. All racks are manufactured to universal 19" standards, providing the ability of use with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel or SUS316 stainless steel. & are shipped fully assembled for quick deployment. CERTECH racks are covered by a 2-year warranty, subject to use within the static loading specifications and operation within normal environmental conditions.


FEATURES


- IP45 Rated
- Smartly designed, fans (with dust filters) are accessible by lifting the pivoting rain hood
- Cable entry plates and glands located on the base panel of racks
- Natural wind cooling through filtered vents on the front door and venting under the lip of the rain hood Fans


DETAILS


| | |
|-------------------------|---|
| Rack Type | Freestanding IP45 rated |
| Static Loading Capacity | 800kgs |
| Colour | Grey or Forest Green* |
| Material | Cold Rolled Steel |
| Mounting Hole Type | Square |
| Security | Lockable front door |
| Assembly | Fully welded construction |
| Warranty (Rack) | 2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions |
| Warranty (Fans) | 1-year warranty |
| Compliance | IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92 |


*Forest Green colour racks are made to order


| NROD188X6FG | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 18RU | | 849mm x 661mm x 1125mm | 880mm x 720mm x 1160mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

| NROD188X6GY | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 18RU | | 849mm x 661mm x 1125mm | 880mm x 720mm x 1160mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

| NROD248X6FG | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 24RU | | 849mm x 661mm x 1385mm | 880mm x 720mm x 1460mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

| NROD248X6GY | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 24RU | | 849mm x 661mm x 1385mm | 880mm x 720mm x 1460mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

| NROD278X6FG | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 27RU | | 849mm x 661mm x 1525mm | 880mm x 720mm x 1560mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

| NROD278X6GY | | RU | WxDxH (External) | Shipping dimensions |
|--|------|----|---|---|
|  | 27RU | | 849mm x 661mm x 1525mm | 880mm x 720mm x 1560mm |
| | | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 375mm | 520mm |
| INCLUDES: 4 x thermostat-controlled fans, accessible via an angled gas-strut rain hood, front & rear adjustable mounting rails | | | | |

