

CERTECH IP45 Rated Stainless Steel Outdoor Rack
Outdoor vented wall mount rack

NRODSWXXXFK



DESCRIPTION

CERTECH IP rated racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. If you need a tough & robust rack, then look no further than the CERTECH IP45 & IP65 rated racks, available in wall mounted & freestanding options. All racks are manufactured to universal 19" standards, providing the ability of use with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel or SUS316 stainless steel*

* SUS316 made to order

FEATURES

- IP45 rated
- Dual exhaust fan drop down tray
- Sealed bottom cable entry gland
- Adjustable 19" mounting rails
- Front door has 130 degrees of movement, swinging from left to right,
- Fully welded design, supplied complete, no assembly required
- Vented double skinned front door

DETAILS

| | |
|----------------------------|---|
| Rack Type | Outdoor wall mounted rack |
| Static Loading Capacity | 60kgs |
| Ventilation | Dual exhaust fan drop down tray and vented double skinned front door |
| Colour | Stainless Steel |
| Material | Cold rolled steel or SUS316* stainless steel (*SUS316 made to order) |
| Mounting Profile Thickness | 2.0mm |
| Mounting Angle Thickness | 1.5mm |
| Surface Finish | Degreasing, pickling, phosphoric wash, cleaning, and powder coated |
| Mounting Hole Type | Square |
| Door Style | Solid steel door |
| Security | Keyed door |
| Assembly | Fully assembled |
| Warranty (Rack) | 2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions |
| Compliance | IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92 |

| NRODWS9400FK | | RU | WxDxH (External) | Shipping dimensions |
|---|--|-----|---|---|
|  | | | 611mm x 465mm x 560mm | 680mm x 520mm x 610mm |
| | | 9RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 240mm | 344mm |

| NRODWS9600FK | | RU | WxDxH (External) | Shipping dimensions |
|---|--|-----|---|---|
|  | | | 611mm x 665mm x 560mm | 680mm x 720mm x 610mm |
| | | 9RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 450mm | 544mm |

| NRODWS12400FK | | RU | WxDxH (External) | Shipping dimensions |
|--|--|------|---|---|
|  | | | 611mm x 465mm x 685mm | 680mm x 520mm x 730mm |
| | | 12RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 240mm | 344mm |

| NRODWS12600FK | | RU | WxDxH (External) | Shipping dimensions |
|---|--|------|---|---|
|  | | | 611mm x 665mm x 685mm | 680mm x 720mm x 730mm |
| | | 12RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 450mm | 544mm |

| NRODWS18400FK | | RU | WxDxH (External) | Shipping dimensions |
|---|--|------|---|---|
|  | | | 611mm x 465mm x 960mm | 680mm x 520mm x 1000mm |
| | | 18RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 240mm | 344mm |

| NRODWS-18600FK | | RU | WxDxH (External) | Shipping dimensions |
|---|--|------|---|---|
|  | | | 611mm x 665mm x 960mm | 680mm x 720mm x 1000mm |
| | | 18RU | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | | 450mm | 544mm |

| NRODWS24400FK | RU | WxDxH (External) | Shipping dimensions |
|---|------|--|--|
|  | 24RU | 611mm x 465mm x 1235mm | 680mm x 520mm x 1280mm |
| | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | 240mm | 344mm |

| NRODWS24600FK | RU | WxDxH (External) | Shipping dimensions |
|---|------|--|--|
|  | 24RU | 611mm x 665mm x 1235mm | 680mm x 720mm x 1280mm |
| | | Set distance between front and rear mounting rails | Max useable space (front to rear door) |
| | | 450mm | 544mm |