

## CERTECH IP45 Rated Outdoor Rack

Outdoor vented wall mount rack

**NRODWXXXFK**



### DESCRIPTION

CERTECH IP rated racks are designed to protect sensitive network equipment from harsh environments where equipment may be exposed to dust or water. If you need a tough & robust rack, then look no further than the CERTECH IP45 & IP65 rated racks, available in wall mounted & freestanding options. All racks are manufactured to universal 19" standards, providing the ability of use with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel or SUS316 stainless steel\*

\* SUS316 made to order

### FEATURES

- IP45 rated
- Dual exhaust fan drop down tray
- Sealed bottom cable entry gland
- Adjustable 19" mounting rails
- Front door has 130 degrees of movement, swinging from left to right,
- Fully welded design, supplied complete, no assembly required
- Vented double skinned front door

### DETAILS

Rack Type	Outdoor wall mounted rack
Static Loading Capacity	60kgs
Ventilation	Dual exhaust fan drop down tray and vented double skinned front door
Colour	Powder coated grey (RAL 7035)
Material	Cold rolled steel or SUS316* stainless steel (*SUS316 made to order)
Mounting Profile Thickness	2.0mm
Mounting Angle Thickness	1.5mm
Surface Finish	Degreasing, pickling, phosphoric wash, cleaning, and powder coated
Mounting Hole Type	Square
Door Style	Solid steel door
Security	Keyed door
Assembly	Fully assembled
Warranty (Rack)	2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions
Compliance	IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92

<b>NRODW9400FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 465mm x 560mm	680mm x 520mm x 610mm
	9RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			240mm	344mm

<b>NRODW9600FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 665mm x 560mm	680mm x 720mm x 610mm
	9RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			450mm	544mm

<b>NRODW12400FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 465mm x 685mm	680mm x 520mm x 730mm
	12RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			240mm	344mm

<b>NRODW12600FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 665mm x 685mm	680mm x 720mm x 730mm
	12RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			450mm	544mm

<b>NRODW18400FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 465mm x 960mm	680mm x 520mm x 1000mm
	18RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			240mm	344mm

<b>NRODW18600FK</b>		<b>RU</b>	<b>WxDxH (External)</b>	<b>Shipping dimensions</b>
			611mm x 665mm x 960mm	680mm x 720mm x 1000mm
	18RU	<b>Set distance between front and rear mounting rails</b>		<b>Max useable space (front to rear door)</b>
			450mm	544mm

**NRODW24400FK**

RU

WxDxH (External)

Shipping dimensions

611mm x 465mm x 1235mm

680mm x 520mm x 1280mm



24RU

Set distance between front and rear mounting rails

Max useable space (front to rear door)

240mm

344mm

**NRODW24600FK**

RU

WxDxH (External)

Shipping dimensions

611mm x 665mm x 1235mm

680mm x 720mm x 1280mm



24RU

Set distance between front and rear mounting rails

Max useable space (front to rear door)

450mm

544mm

