

DoE NETWORK SERVER RACKS

Premier Series 19" Network Racks - 800mm Wide

NSRXX8XX-DOE



DESCRIPTION

CERTECH DoE racks are manufactured around universal 19" standards, providing the ability to use our racks with universal 19" equipment from vendors worldwide. All racks are constructed from high quality cold rolled steel & are shipped fully assembled for quick deployment.

STANDARDS

- Complies with IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/T3047.2-92, IP20 rated

PRODUCT SPECIFICATIONS

Product Type	DoE NSR Premier Series
Static Loading Capacity:	800kgs
Colour:	Black (RAL 9004) powder coated paint
Material:	SPCC quality cold rolled steel, gloss black colour, easy clean surface
Mounting Profile Thickness:	2.0mm
Mounting Angle Thickness:	1.5mm
Surface Finish:	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Mounting Hole Type:	Square
Door Style:	Bi-fold front and rear perforated steel, honeycomb style
Side Panels:	Single piece, lockable & removable
Security:	Keyed alike doors & side panels
Assembly:	Supplied complete
Compliance:	IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92

FEATURES

- Static loading: 800kg
- Width: 800mm
- Compatible with 19" International Standard and Metrical and ETSI standards
- 2 year warranty on cabinets. Subject to use within the static loading specifications and operation within normal environmental conditions

NSR278X8-DOE	RU	WxDxH (External)	Shipping dimensions
		800mm x 800mm x 1410mm	890mm x 900mm x 1425mm
	27RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)
		485mm	720mm
Vertical cable ducts, 4-way fan kit, 1 x fixed shelf & 6-outlet 10A horizontal PDU w/ 10A Plug			

NSR458X8-DOE	RU	WxDxH (External)	Shipping dimensions
		800mm x 800mm x 2210mm	890mm x 900mm x 2225mm
	45RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)
		485mm	720mm
Vertical cable ducts, 4-way fan kit, 1 x fixed shelf & 10-outlet 10A vertical PDU w/ 15A Captive Plug			

NSR458X10-DOE	RU	WxDxH (External)	Shipping dimensions
		800mm x 1000mm x 2210mm	890mm x 1100mm x 2225mm
	45RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)
		685mm	920mm
Vertical cable ducts, 4-way fan kit, 1 x fixed shelf & 10-outlet 10A vertical PDU w/ 15A Captive Plug			



Lockable, removable side panels



Multiple grounding pins to earth doors and side panels

