

SWING FRAME WALL MOUNT RACKS

Server Racks - Wall Mount

NCSWGXXX



DESCRIPTION

CERTECH Double Section Wall Mount Series racks are the perfect wall mount rack for any small home office/business installation, where access to the rear of the rack is required. All racks are manufactured around universal 19" standards, providing the ability to use our racks with universal 19" equipment from other vendors & manufacturers. All racks are constructed from high quality cold rolled steel & are shipped fully assembled for quick deployment. CERTECH racks are covered by a 2-year warranty, subject to use within the static loading specifications and operation within normal environmental conditions.

FEATURES

- Front Glass Door
- Fans (drop-down tray)
- Cable Entry
- Adjustable Vertical Mounting Rails
- Rear Swing Frame
- Integrated Earthing

DETAILS

Rack Type	Double Section Wall Mount Series
Static Loading Capacity	60kgs
Colour	Black (RAL 9004) powder coated paint
Material	SPCC quality cold rolled steel, easy clean surface
Mounting Profile Thickness	2.0mm
Mounting Angle Thickness	1.5mm
Surface Finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Mounting Hole Type	Square
Door Style	Australian approved toughened glass front door
Side Panels	Single piece, removable
Security	Keyed alike doors & side panels
Assembly	Fully assembled
Warranty (Rack)	2-year warranty. Subject to use within the static loading specifications and operation within normal environmental conditions
Warranty (Fans)	1-year warranty
Compliance	IEC-60297, ANSI/EIA RS-310-D, IEC297-2, DIN41491-1, DIN41494-7, GB/T3047.2-92

	NCSWG4450	RU	WxDxH (External)	Shipping dimensions
			600mm x 450mm x 278mm	660mm x 510mm x 320mm
	4RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		190mm	400mm	
	INCLUDES: 10 x cage nuts			
	NCSWG6450	RU	WxDxH (External)	Shipping dimensions
			600mm x 450mm x 366mm	660mm x 510mm x 405mm
	6RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		190mm	400mm	
	INCLUDES: 1 x shelf, 10 x cage nuts			
	NCSWG6550	RU	WxDxH (External)	Shipping dimensions
			600mm x 550mm x 366mm	660mm x 610mm x 405mm
	6RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		285mm	500mm	
	INCLUDES: 2 x fans, 1 x shelf, 10 x cage nuts			
	NCSWG9550	RU	WxDxH (External)	Shipping dimensions
			600mm x 550mm x 500mm	660mm x 610mm x 530mm
	9RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		285mm	500mm	
	INCLUDES: 2 x fans, 1 x shelf, 10 x cage nuts			
	NCSWG9600	RU	WxDxH (External)	Shipping dimensions
			600mm x 600mm x 500mm	660mm x 660mm x 530mm
	9RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		335mm	550mm	
	INCLUDES: 2 x fans, 1 x shelf, 10 x cage nuts			
	NCSWG12550	RU	WxDxH (External)	Shipping dimensions
			600mm x 550mm x 650mm	660mm x 610mm x 680mm
	12RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		285mm	500mm	
	INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			
	NCSWG12600	RU	WxDxH (External)	Shipping dimensions
			600mm x 600mm x 650mm	660mm x 660mm x 680mm
	12RU	Set distance between front and rear mounting rails	Max useable space (front to rear door)	
		335mm	550mm	
	INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG15600	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 600mm x 775mm	660mm x 660mm x 820mm
15RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		335mm	550mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG18550	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 550mm x 908mm	660mm x 610mm x 960mm
18RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		285mm	500mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG18600	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 600mm x 908mm	660mm x 660mm x 960mm
18RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		335mm	550mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG24550	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 550mm x 1175mm	660mm x 610mm x 1220mm
24RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		285mm	500mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG24600	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 600mm x 1175mm	660mm x 660mm x 1220mm
24RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		335mm	550mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			

NCSWG27600	RU	WxDxH (External)	Shipping dimensions
------------	----	------------------	---------------------



		600mm x 600mm x 1308mm	660mm x 660mm x 1360mm
27RU		Set distance between front and rear mounting rails	Max useable space (front to rear door)
		335mm	550mm
INCLUDES: 2 x fans, 1 x shelf, 20 x cage nuts, 1 x horizontal 6 outlet PDU			