

Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees

JWPC6XX

FEATURES:

High Performance Cat6 UTP Jack, Australian style.

Performance:

Meets Cat6 EIA/TIA 568B.1 Standards

Materials:

- Plastic Body: Fireproof ABS UL-94V0
- RJ-45 Jack: 8P8C micro inches gold plated
- PCB: FR-4 / 1.0mm UL94V0
- IDC Body: Fireproof ABS UL-94V0
- IDC Pin: Bronze & Tinned
- Label Colour Code: T568A

IDC Description:

- For 22-26 AWG
- For 110 or Krone punch down tool

Electrical Specifications:

- Insulation Resistance: 500m ohms (min)
- Contact Resistance: 20m ohms (max)
- Current Rating: 1.5 Amps
- DC Resistance: 0.1 ohm (max)
- Withstanding Voltage: 1000 VAC RMS @ 60Hz / 1 min

Mechanical Specifications:

- IDC Punch Down Cycle: Over 250 Cycles (min)
- RJ-45 Jack Insertion Cycle: Over 2000 Cycles (min)
- Operating Temperature: -40 ~ +70 Degrees Celcius



Model Code	Description	Colour	Category
JWPC6BK	Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees	Black	CAT6
JWPC6BL	Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees	Blue	CAT6
JWPC6GN	Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees	Green	CAT6
JWPC6RD	Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees	Red	CAT6
JWPC6YL	Cat6 UTP RJ45 Wall Plate Jack, 180 Degrees	Yellow	CAT6