

## CERTECH Cat6 RJ45 23AWG Plug 50pc Jar, Round Solid Shielded

**RJ45C6SR23JAR**

### FEATURES:

#### ELECTRICAL:

- UL APPLICATIONS:250 VOLTS AC MAX AT 2 AMPS.
- DIELECTRIC WITHSTANDING VOLTAGE:1000 VOLTS AC.
- WITHSTAND VOLTAGE TIME:60S.
- INSULATION RESISTANCE:500MΩ.
- TERMINATION: RESISTANCE 20mΩ MAX AFTER ENVIRONMENTAL TESTING.

#### MECHANICAL:

- CABLE-TO-PLUG TENSILE STRENGTH: 20 POUND MIN.
- DURABILITY:200 MATING CYCLES.

#### MATERIAL:

- HOUSING:POLYCARBONATE,UL94V-0.
- COLOR:TRANSPARENT OR OTHER COLOUR ARE AVAILABLE.
- CONTACT BLADE:COPPER ALLOY.
- GOLD PLATING : 3U"-50U",ARE AVAILABLE.

#### USAGE:

- CONDUCTOR:STRANDED & SOLID WIRE.
- (It can be used for the wire OD from  $\phi 1.35$ - $\phi 1.45$ ).



| MODEL         | DESCRIPTION                                                 | TYPE |
|---------------|-------------------------------------------------------------|------|
| RJ45C6SR23JAR | CERTECH Cat6 RJ45 23AWG Plug 50pc Jar, Round Solid Shielded | Cat6 |

**RJ45C6SR23JAR**

