

Network Management Cards



While PowerShield UPSs do their job of holding up critical electronic equipment, behind the scenes, PowerShield proprietary software and management cards are there to manage and record critical power events, so that managers can be aware and informed of problems in real time. The Communications cards and devices, together with the software solutions allow for automatic graceful shutdown of programs and devices in the event power outages last longer than their nominated time.

SNMP Card

The **SNMP** (Simple Network Management Protocol) card allows the UPS to be directly connected to the network, without the need of a local computer. Furthermore, the SNMP card contains an integrated web server CPU, allowing the IT Manager to view and control the UPS and power events with any standard internet browser. This card is easily configured for virtual machine environments such as VMware and HyperV.



PSEMD

The **PowerShield Environmental Monitoring Device** (PSEMD) is a PSSNMPV4 accessory suited for monitoring temperature and humidity. Email alerts and or system shutdown can be initiated if the user defined thresholds are exceeded. It offers two additional dry contact inputs for sensors such as smoke detectors and tamper switches.



Relay Card

PSAS400T (Terminal Strip) or
PSAS400D (D-type connector)

The **Relay Card** (PSAS400) provides VFC (Volt Free Contact) relays that change state upon UPS events. This type of card is often used when current loop communications are required for devices such as BMS (Building Management Systems), Access Control Alarm Panels or Industrial PLCs. User selectable normally open (default) or normally closed contacts.



Modbus Card

The **PowerShield Modbus Card** (PSMbus) facilitates UPS communication with industrial and building management systems using the Modbus RTU Protocol. PSMbus card provides real time monitoring and control of multiple UPS's via the RS485 communications port.



SNMP Agent Controller

NetAgent 9 DX630 supports USB to SNMP conversion to enable comprehensive, easy-to understand and secure remote monitoring and management for UPS equipment via the internet.

It is ideal support for PowerShield UPS models SafeGuard 750, Defender 650, Defender Rack 800, Defender 1200, Defender 1600 and more.



External Comms Box

The PowerShield external Comms Box (PSECB) allows two comms cards to be operational, whilst using the UPS intelligent slot and PSECB over UPS serial port simultaneously. Includes a 240Vac / 12Vdc power pack.

Optional Accessory

PowerShield External Comms Box
(PSSNMPv4, PSAS400, PSMbus)



DESIGNED BY AUSTRALIANS FOR AUSTRALIAN CONDITIONS

