

HDMISP8K1-2



DESCRIPTION

This product is an 8K HDMI splitter that splits one HDMI input signal to two HDMI output signals. Adopting the latest standard HDMI2.1, the video signal transmission is as high as 8K@60Hz/4K@120Hz/1080p@240Hz. With HDR10+, Dolby Vision high dynamic range image and variable refresh rate (VRR), the screen display is more delicate and smooth, which can be widely used in TV stores, cinemas, outdoor advertising and home entertainment.

FEATURES

- 8K@60Hz
- 4K@120Hz
- VRR
- S/PDIF Output Port
- 3D
- Micro USB Upgrade
- Dolby Vision/Audio
- CEC

DETAILS

HDMI Input	1x HDMI
HDMI Output	2x HDMI
Compatibility	HDMI 2.1, HDMI2.0, HDMI1.4 HDCP 2.3, HDCP2.2, HDCP1.4
Maximum transmission rate	48Gbps
Resolutions	7680x4320@24/25/30/50/60Hz 3840x2160@24/25/30/50/60/120Hz 1080p@24/25/30/50/60/120Hz 720p@50/60/100/120Hz
Video signal	EDID passthrough, auto downscaling
Video signal	HDR10/HDR10+/Dolby Vision
Video signal	HDMI 3D
Video signal	HDMI CEC
Video signal	VRR, Free Sync, G-Sync
S/PDIF Output	Dolby Atmos, Dolby True HD, DTS:X, DTS-HD, etc.
HDMI Output	Dolby Atmos, Dolby Digital 7.1CH, Dolby True HD, DTS:X, DTS-HD, LPCM 7.1CH, etc.
Power Supply	DC5V/1A
Power Consumption	<4W
Working temperature	-20°C~60°C
Storage temperature	-30°C~70°C
Humidity	0~90%RH (No condensation)

DETAILS

Weight	200g
Colour	Black
Dimensions	135.0(L)*54.0(W)*16.5(H)mm
Protection	ESD protection 1a Contact discharge level 2 (± 4 KV) 1b Air discharge level 3 (± 8 KV) Implementation of the standard: IEC61000-4-2 Lightning protection, Surge protection

