

Line Interactive UPS

Uluru Series



600VA - 2000VA



Features:

- AVR boost and buck
- Cold start function
- USB interface for power management
- Built-in self-diagnosis function
- Modem/LAN internet protection
- User friendly LCD display
- Fastest charging capacity
- Auto charge even when UPS is turned off
- Auto restart on resumption of AC supply

Line Interactive UPS

UPS SPECIFICATIONS:

MODEL		Uluru 600	Uluru 800	Uluru 1200	Uluru 1500	Uluru 2000
CAPACITY	VA/W	600VA/360W	800VA/480W	1200VA/720W	1500VA/900W	2000VA/1200W
INPUT	Voltage	110/120VAC or 220/230/240 VAC				
	Voltage Range	81 - 145VAC / 162 - 290VAC				
	Frequency Range	60/50Hz (auto sensing)				
OUTPUT	AC Voltage Regulation (Battery Mode)	±10%				
	Frequency Range (Battery Mode)	60Hz or 50Hz ±1Hz				
	Transfer Time	Typically 2 - 6ms, 10ms maximum				
	Waveform (Battery Mode)	Simulated Sine Wave				
BATTERY	Battery Type	12V 7Ah	12V 9Ah	12V 7Ah	12V 9Ah	
	Number of Internal Batteries	1	1	2	2	
	Typical Recharge Time	6 - 8 hours recovery to 90% capacity				
INDICATORS	LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Low Battery				
PROTECTION	Full Protection	Discharge, overcharge and overload protection				
ALARM	Battery Mode	Sounding every 10 seconds				
	Low Battery	Sounding every second				
	Overload	Sounding every 0.5 second				
	Battery Replacement Alarm	Sounding every 2 seconds				
	Fault	Continuously sounding				
PHYSICAL	Dimension (WxHxD) mm	101 x 142 x 298		149.3 x 162 x 338	158 x 198 x 380	
	Net Weight (kg)	4.25	4.9	8	11.1	11.5
OPERATING ENVIRONMENT	Humidity	0 - 90% RH at 0 - 40°C (non-condensing)				
	Noise Level	Less than 40dB				
MANAGEMENT	Optional USB / RS-232 Port	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC				
* Product specifications are subject to change without further notice						