

# DOT 9100 LED

A dynamic stylish, versatile high specification downlight using the latest in LED technology.



### Specification

- Available in two formats, 350mA and 500mA remote electronic driver.
- The 350mA format is an 18W 1100Lm system, that offers 51Lm/W
- The 500mA format is a 24W 1500Lm system, that offers 48Lm/W
- The dimensions are 152mm deep, 92mm cut-out and 105mm overall face diameter
- The downlight has a low glare specular polished silver reflector which has a wide beam distribution of 70 degrees
- The downlight is designed with an integral heat sink system
- It is compatible with the Axlock accessory range
- Conveniently wired with a flex & plug
- Can be dimmed via DALI, push dim or analogue
- The system is rated to 25 degree and has an average rated life of 44,000 hrs
- Both formats are available in 3000K and 4000K
- Compliant to AS/NZSCISPR15 and IEC/ENC61347.2.13, AS/NZS 60598



### Quick Spec

The Pierlite DOT recessed LED 18W or 24W dimmable downlight, on board heat sink, remote electronic driver and flex and plug, compatible with Axlock accessories

### Design Application

Designed to suit commercial spaces, receptions areas, meeting rooms, foyers, health environments, hotel spaces and high end residential

### Product Codes

Code	Version	Dim (mm)	Mass (kg)
9136/40/921	18W 4K WH Soft Diffuse	105 x 152	0.8
9156/40/921	24W 4K WH Soft Diffuse	105 x 152	0.8
9156/30/921	24W 3K WH Soft Diffuse	105 x 152	0.8
9136/30/921	18W 3K WH Soft Diffuse	105 x 152	0.8
9156/40/920	24W 4K WH 500mA	105 x 152	0.8
9136/40/920	18W 4K WH 350mA	105 x 152	0.8
9156/30/920	24W 3K WH 500mA	105 x 152	0.8
9136/30/920	18W 3K WH 350mA	105 x 152	0.8

### Performance

