



CLEVERTRONICS ECONOMY LED WEATHERPROOF EXIT



PRODUCT INFORMATION

Catalogue Number	EWELED
Description	LED Economy weatherproof EXIT
Construction	Polycarbonate clear cover, Glass reinforced nylon PA66 base
Mounting	Wall, Ceiling single-sided & Ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Charging Method	Constant Current (16hrs); Pulse Charge (Standby)
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 50,000 hours
Operating Voltage	250V AC; 50Hz
Power Consumption	3.0 Watts (Standby)
IP Rating	IP66/67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E2
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1510325	4xAA NiCad Battery Pk. 800mAh Stick
8002271	PCA:ECO Cleverfit Driver #HT10150-A5S
8002291	PCA:ECO CleverfitLEDBoard,HT10152-A5s,V2