



## CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT (DALI)



### PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SMS-DALI
Description	LP Premium LifeLight PRO, High Performance, Surface Mounted Emergency Light with Lithium Battery Technology
Mounting	Surface Mount
Dimensions L x W x H	267mm x 148mm x 60mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-SMS-CKIT-NP	LifelightPro,Control Only, LP, NP
1100830	Lifelight Pro Head Assembly, Round
8002200	PCA:DALI Node, #CT10410-A3

**DALI EM****LP** LITHIUM IRON  
PHOSPHATE**PREMIUM**

PROVEN PROJECT PERFORMANCE