

LED 3528 STRIP KITS IP65 (2M & 5M)



PRODUCT SPECIFICATIONS

- Input voltage: 12V DC
- SMD3528 LED chips (60pcs per meter)
- Wattage: 4.8W per meter
- Power factor: ≥ 0.05
- Life time: 20.000hrs
- Dimensions: W 8mm x D 2mm
- 3M tape
- Wall plug in driver (please see the diagram)
- Beam angle: 120°
- IP rating: IP65 for LED strip only; IP20 for connector & driver
- Ambient temp: -25 to 60°C
- Not suitable for dimming
- 2 year replacement warranty

IP20	IP20					IP65															
LED DRIVER	12V DC	Male Female JOINER PLUG	= 0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



3000K

NOTE:

- Tail connector & LED driver IP20 only
- Not suitable for diffused channels
- Installation surface must be smooth, clean and dry
- The LED strip can not be joined
- Strip can be cut at the cutting lines
- Strip not suitable for going around corners

Part No.	LED QTY	Kelvin	elvin Total Power		Lumens	Current	Package	Dimensions	
2M3K352860IP65	120pcs	3000K	9.6W	>80	800lm	1.0A	2m/reel	2000x8x2mm	
2M5K352860IP65	120pcs	5000K	9.6W	>80	850lm	1.0A	2m/reel	2000x8x2mm	
5M3K352860IP65	300pcs	3000K	24W	>80	2000lm	2.0A	5m/reel	5000x8x2mm	
5M5K352860IP65	300pcs	5000K	24W	>80	2120lm	2.0A	5m/reel	5000x8x2mm	

UPDATED ON 16.05.2017

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au Website: www.clalighting.com.au



Follow us: facebook.com/CLALighting

CLA LIGHTING