

## MR16 EXTERIOR 12V INGROUN UP LIGHTERS (small faceplates)



### PRODUCT FEATURES


- Input voltage : 12-25V DC / AC
- External Control Gear Required
- Faceplate: 316 stainless steel or solid copper
- Housing: 316 stainless steel or solid copper
- Lamp holder: MR16 (Max 20W halogen globe)
- Globe not included
- Plastic sleeve included (must be installed)
- Fitting slides into sleeve and remains unattached
- Cable included (L950mm)




IGMEYEC



IGMEYESS



IGMEYC, EYESS



IGMGRSS, SMC, SMSS



IGMSMC



IGMSMSS



IGMGRSS

|          |                                             |
|----------|---------------------------------------------|
| IGMEYEC  | 4mm Tempered Glass. Max load capacity 100Kg |
| IGMEYESS | 4mm Tempered Glass. Max load capacity 100Kg |
| IGMSMC   | 4mm Tempered Glass. Max load capacity 600Kg |
| IGMSMSS  | 4mm Tempered Glass. Max load capacity 600Kg |
| IGMGRSS  | 4mm Tempered Glass. Max load capacity 600Kg |

| PART NO. | DESCRIPTION                                          | COLOUR                             | WEIGHT (KG) | BOX (CM)     | CARTON QTY |
|----------|------------------------------------------------------|------------------------------------|-------------|--------------|------------|
| IGMGRSS  | INGROUND / WALL Grilled MR16 12V SS316 RND           | 316 Stainless steel clear anodized | 0.4         | 13 x 10 x 10 | 1/20       |
| IGMEYEC  | INGROUND / WALL EYELID MR16 12V COP RND              | Polished copper                    | 0.8         | 16 x 10 x 10 | 1/20       |
| IGMEYESS | INGROUND / WALL EYELID MR16 12V SS316 RND            | 316 Stainless steel clear anodized | 0.7         | 16 x 10 x 10 | 1/20       |
| IGMSMC   | INGROUND UPLIGHTER / OPEN WALL MR16 12V COP SM RND   | Polished copper                    | 0.4         | 13 x 10 x 10 | 1/20       |
| IGMSMSS  | INGROUND UPLIGHTER / OPEN WALL MR16 12V SS316 SM RND | 316 Stainless steel clear anodized | 0.4         | 13 x 10 x 10 | 1/20       |