

FPC-15900 & FPC-15905 - DOL STARTER

HARDWARE FEATURES

Enclosure:

- IP54 weatherproof rating
- Powder coated mild steel
- Removable gland plate

Protection:

- Padlockable mains power isolator switch
- Circuit breaker protected low voltage control and input circuitry
- Contactor and thermal overload protection of pumps

Control & interface:

- Selector switch for auto/off/manual operation of pump

Inputs:

- 2x 24Vac inputs for cut off and working level float switches

Outputs:

- 1x pump supply output

FUNCTION FEATURES

Operation:

- Simple start and stop operation of pump

Fault protection:

- Pump overload shut-down



SINGLE PHASE (230 VAC) - FPC-15900 RANGE

Code	Overload Rating	Enclosure Size
FPC-15900-AA	1.6 - 2.5 Amp	300x300x150mm
FPC-15900-A	2.5 - 4 Amp	300x300x150mm
FPC-15900-B	4 - 6 Amp	300x300x150mm
FPC-15900-BB	5.5 - 8 Amp	300x300x150mm
FPC-15900-C	7 - 10 Amp	300x300x150mm
FPC-15900-D	9 - 13 Amp	300x300x150mm
FPC-15900-E	12 - 18 Amp	300x300x150mm

THREE PHASE (400 VAC) - FPC-15905 RANGE

Code	Overload Rating	Enclosure Size
FPC-15905-AA	1.6 - 2.5 Amp	300x300x150mm
FPC-15905-A	2.5 - 4 Amp	300x300x150mm
FPC-15905-B	4 - 6 Amp	300x300x150mm
FPC-15905-BB	5.5 - 8 Amp	300x300x150mm
FPC-15905-C	7 - 10 Amp	300x300x150mm
FPC-15905-D	9 - 13 Amp	300x300x150mm
FPC-15905-E	12 - 18 Amp	300x300x150mm

Additional overload ratings available on request